


ITEM NO.	springclip/ QTY.	Title	drwnum	partnum
1	1	Lock Assembly	1050.M.09.01_4.expl	PCCL19-19
2	1	O-Ring, ID14 x 2	-	BB/OR-14 x 2
3	1	Camlock Cover Base	1050.M.02.21_2	DOMCEN0480
4	1	Camlock Cover Lid	1050.M.02.22_2	DOMCEN0480
5	1	Camlock Logo Spacer	1050.M.01.09.28_6	1050M10928

Rev_10 2008/04/15, GR: Used Push Clip Cam Lock,
was a 16mm std lock with lock nut.
Rev_9 2007/09/27, GR: Updated requirements.

Material: See table	- All dimensions in mm. - Deburr all sharp edges - General tolerances: Linear: ±0.125 Shafts: -0.250 to 0 Bores: 0 to 0.250 Angular: ±2°	Drg. mass: 105.85 g Drawn by: G.R. Last mod: 2008/04/15 Scale: Not to any scale Part No: 1050M19000
Corrosion protection: None		
 CENTURION Tel: (011) 699-2400 Fax: (011) 704-3412	Title: Sheet 1 of 1 Drg. No. & Revision: 1050.M.01.09.00_10.Exp	Camlock assy

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CENTURION SYSTEMS ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF CENTURION SYSTEMS IS PROHIBITED